

NANOCAL Series The best tool for ISO length calibration



- GBC-NANOCAL Gauge Block Comparator is specially designed for the calibration or dimensional inspection of gauge blocks with nominal lengths ranging from 0.1 to 300mm.
- GBC-NANOCAL The configuration, which consists of two high-precision inductive probes aligned opposite one another with 0.01 µm display. The measuring system provides full guarantee for an extra low uncertainty of measurement.
- Although METROLOGY GBC-NANOCAL Gauge Block Comparator is mainly intended for manufacturers and end-users of gauge blocks, this comparator is also widely used in ISO/IEC 17025 national accredited calibration laboratories all over the world.

Length metrology standard--- The best and only choice for gauge blocks calibration

Model No.	Measuring Range	Resolution	Repeatability	Uncertainty of Measurement (um)
GBC-P100	0.1~100mm	0.01um	≦0.025um	U95 \leq ±(0.05+0.5L/1000) Reference Temperature 20 ± 1°C
GBC-P300	0.1~300mm	0.000001"		U95 \leq ±(0.03+0.3L/1000) Reference Temperature 20 ± 0.5°C





Innovation Research & Development Design Manufacture Assembly Inspection

GBC-NANOCAL Measuring system combinations

Measuring stand

DIN 00 grade 300x200x75mm granite base stand, heavy construction with height toothed rack guide column plug two hand wheel for coarse and fine adjustment setting of the measuring arm

Measuring table

Made from hardened tool steel and fitted with 6 antimagnetic ceramic cylindrical pins for a safe positioning which provide high protection, and wear resistance to the gauge blocks over years.

Single template system

Used to shift the gauge blocks from a given point to another. With two interchangeable templates, one is for gauge blocks 9x30mm and another one is for gauge blocks 9x35mm

Special template system

For shifting the long gauge blocks from a given point to another. With one template and three support device for length >100mm long gauge blocks 9x35mm.(for GBC-P300)

Measuring system

Consisting of: Upper probe A. Measuring force to 1N and lower probe B. Measuring force to 0.63N, fitted with the tungsten carbide measuring insert with spherical measuring face R=20mm.



Innovation Design R&D Patented Technology Award











METRULOGY



Innovation Design R&D Patented Technology Award



Innovation Research & Development Design Manufacture Assembly Inspection

GBC-NANOCAL Measuring system combinations

Heat protection shield

Dimension: 250x380x6mm Screen material: Anti-Shatter fiber glass For blocking temperature influence caused from operator.

Electric vacuum pump with foot switch

For retracting the measuring bolt of each probe. Power: 100-240 Vac, 50-60Hz

Pneumatic suction loader

For safe, easy handling of small gauge blocks with nominal lengths up to 5mm. (optional)

Length measuring system

Instrument TT 80 with RS232 interface and analogue output with 0.01um resolution. Power: 100-240 Vac, 50-60Hz

- 2 of probe inputs (Automatic conversion)
- 9 of measuring ranges (Automatic conversion) Lowest Value: ± 0.5µm, Highest Value: ± 5000µm
- Digital and analogue display (metric/inch unit system) Resolution : 0.01um











